

TECHNICAL DATA SHEET

METALLIC PAINT

DESCRIPTION

sparkling metallic effect, wash-resistant wall paint, for a glittering light reflecting finish on walls and ceilings. For interior use.

- Will cover in 1 to 2 layers depending on the substrate
- Breathable
- Scrub-resistant
- Glossy
- Very decorative
- Easy to apply

USE

Can be applied to painted walls and ceilings.

Paint takes 28 days to “cure” or fully harden. Ensure you do not clean or compromise the paint until this time has lapsed (most relevant for use in bathrooms – use of showers/baths/other moisture sources within this period means we may not be able to guarantee durability or washability).

COLOUR

Available in specific metallic colours produced on the Graham & Brown colour mixing machine.

APPLICATION AND HANDLING

In addition to walls, also suitable for painting fibreglass fabric and ornamental plaster. Suitable substrates: cement and plasterwork, concrete, brickwork, plasterboard, MDF.

Stir thoroughly prior to use. Apply in 1 or 2 coats with a square pasting brush, woolly roller or airless spray. Do not dilute.

COVERAGE

According to ISO-6504-3 and DIN EN 13300 approx. 9 m²/litre per coat, depending on the substrate. Deposition efficiency: Class 1

DRYING

23°C and 65% relative humidity. Dust-dry after approx. 2 hours.

Can be painted over after approx. 6 hours.

APPLICATION ADVICE

GENERAL

Surfaces must be clean, dry and free from dust or grease. Sand and repair surface irregularities. Remove and/or repair all loose and unstable coats.

SUBSTRATES STAINED BY NICOTINE, DAMP, RUST OR SOOT

- Wash with water and a degreasing agent and allow to dry well.
- Next, seal the surface of the substrate with Sealing Primer.

TECHNICAL DATA

Binding agent	Synthetic resin dispersion
Pigments	Aluminium flakes and mineral fillers
Solvent	Water
Solid components	19% by weight
Specific mass	Approximately 1 g/ml
Viscosity	Viscolab LC 3: 4.0 PaS @ 20°C
Fineness	25 microns; ISO-787-7 and DIN EN 13300 fine
Degree of gloss	Medium gloss ISO-2813 and DIN EN 13300: 60°/43% 85°/54%
Tint	Metallic colours

Hazard classification	See MSDS
Tool cleaning instructions	Use water and soap

FEATURES

Scrub-resistant according to DIN 53778: 10,000 cycles, class S.

Scrub-resistance to ISO-11998 and DIN EN 13300: Class 2

STORAGE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

GENERAL

Do not use at temperatures below +8°C. Allow newly cemented surfaces to set for at least 6 weeks. Slight colour deviations are possible due to the use of natural ingredients. To minimise this, we recommend that materials with a different batch code are mixed together first. Always work wet-on-wet to prevent visible brush strokes.

SURPLUS PRODUCT

This product and the packaging should be disposed of at a collection point for hazardous or special waste.