

## TECHNICAL DATA SHEET

## PRIMER AND UNDERCOAT

---

### DESCRIPTION

Quick drying, good filler. Excellent hiding power. Low in odour and virtually solvent-free. Easy to sand. Even coverage. Insulating. For interior use.

### USE

For wood, MDF, board, primed metal, plasterwork and rigid plastic

### APPLICATION

Stir well before use. Apply 2 full coats with an acrylic brush/roller or varnish roller. Dilute the first layer on untreated wood with up to 3% of water as required. Apply the second layer undiluted. Lightly sand and remove any dust between the coats. Do not apply to large surfaces simultaneously and always work wet-on-wet due to the quick drying properties of the product.

### COVERAGE

11-13 m<sup>2</sup> litre per coat depending on the object to be painted and the application method.

### DRYING

23°C and 65% relative humidity. Dust-dry after approximately 1 hour. Can be painted over after approximately 6 hours. Wood types that bleed can be painted over after at least 16 hours.

## SYSTEM CONSTRUCTION

### GENERAL

The surface must be clean, dry and free from dust or grease. Slightly round off sharp corners to obtain good edge coverage.

### UNPAINTED WOOD AND MDF

- Degrease, sand lightly and remove any dust.

### METAL

- Degrease, remove all rust and make area free of dust. Treat with antirust red oxide primer.
- Next apply an intermediate coat of Primer and Undercoat.

### RIGID PLASTIC

- Degrease, remove all dust. Treat with plastic primer.
- Next, apply an intermediate coat of Primer and Undercoat.

### PLASTERWORK

- Degrease, remove all dust.
- Next, apply an intermediate coat of Primer and Undercoat.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact Graham and Brown Customer Service.

## TECHNICAL DATA

Binding agent	Acrylic dispersion
Pigments	Rutile titanium dioxide and mineral extenders
Solvent	Water
Solid components	53% by weight
Specific mass	Approximately 1.35 g/ml
Viscosity	Krebs Stormer 90 KU @ +20°C

Fineness	20 microns
Recommended coat thickness	35 microns dry
Degree of gloss	Matt
Tint	White
Dilute with	Water
Hazard classification	See MSDS
Tool cleaning instructions	Use water and soap

## **PERFORMANCE**

Primer with good filling properties, for interior use. Can even be recoated on the same day.

## **STORAGE**

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

## **GENERAL**

Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area. Do not close doors and windows until the paint has dried fully (after a minimum of 8 hours).

## **SURPLUS PRODUCT**

This product and the packaging should be disposed of at a collection point for hazardous or special waste.