

TECHNICAL DATA SHEET

PRIMER AND UNDERCOAT

DESCRIPTION

Quick drying, good filler. Excellent hiding power. Low in odour and virtually solvent-free. Easy to sand. Even coverage. Insulating. For interior use.

USE

For wood, MDF, board, primed metal, plasterwork and rigid plastic

APPLICATION

Stir well before use. Apply 2 full coats with an acrylic brush/roller or varnish roller. Dilute the first layer on untreated wood with up to 3% of water as required. Apply the second layer undiluted. Lightly sand and remove any dust between the coats. Do not apply to large surfaces simultaneously and always work wet-on-wet due to the quick drying properties of the product.

COVERAGE

140ft² /quart per coat depending on the object to be painted and the application method.

DRYING

73°F and 65% relative humidity. Dust-dry after approximately 1 hour. Can be painted over after approximately 6 hours. Wood types that bleed can be painted over after at least 16 hours.

APPLICATION ADVICE

GENERAL

The surface must be clean, dry and free from dust or grease. Slightly round off sharp corners to obtain good edge coverage.

UNPAINTED WOOD AND MDF

- Degrease, sand lightly and remove any dust.

METAL

- Degrease, remove all rust and make area free of dust. Treat with antirust red oxide primer.
- Next apply an intermediate coat of Primer and Undercoat.

RIGID PLASTIC

- Degrease, remove all dust. Treat with plastic primer.
- Next, apply an intermediate coat of Primer and Undercoat.

PLASTERWORK

- Degrease, remove all dust.
- Next, apply an intermediate coat of Primer and Undercoat.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact Graham and Brown Customer Service.

TECHNICAL DATA

Binding agent	Acrylic dispersion
Pigments	Rutile titanium dioxide and mineral extenders
Solvent	Water
Solid components	53% by weight
Specific mass	Approximately 1.35 g/ml
Viscosity	Krebs Stormer 90 KU @ +20°C

Fineness	20 microns
Recommended coat thickness	35 microns dry
Degree of gloss	Matt
Tint	White
Dilute with	Water
Hazard classification	See MSDS
Tool cleaning instructions	Use water and soap

PERFORMANCE

Primer with good filling properties, for interior use. Can even be recoated on the same day.

STORAGE

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

GENERAL

Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area. Do not close doors and windows until the paint has dried fully (after a minimum of 8 hours).

SURPLUS PRODUCT

This product and the packaging should be disposed of at a collection point for hazardous or special waste.