

## TECHNICAL DATA SHEET

## GLITTER TOPCOAT

---

### DESCRIPTION

Acrylic-based wall varnish with glitter gloss. For a sparkling finish for painted walls and wood. Also protects walls painted in a dark colour. For interior use.

### USE

Can be applied to painted walls and wood.

Paint takes 28 days to “cure” or fully harden. Ensure you do not clean or compromise the paint until this time has lapsed (most relevant for use in bathrooms – use of showers/baths/other moisture sources within this period means we may not be able to guarantee durability or washability).

### COLOUR

Available in gold and disco colours.

### APPLICATION AND HANDLING

Stir thoroughly prior to use. Apply 1 to 3 coats using an acrylic paint brush, acrylic paint roller or paint sprayer. Do not dilute. Always apply wet-in-wet to avoid visible strokes.

### COVERAGE

Approx. 18 m<sup>2</sup>/litre per coat depending on the object to be painted and the application method.

### DRYING

23°C and 65% relative humidity. Dust-dry after approximately 1 hour. Can be painted over after approximately 4 hours.

## APPLICATION ADVICE

### GENERAL

Surfaces must be clean, dry and free from dust or grease.

### UNTREATED WOOD

- Degrease, sand lightly and remove any dust. Round off sharp edges to maximise adhesion.
- Next apply 2 or 3 coats of the topcoat.

### PAINTED WALLS

- Carefully degrease with a degreasing agent and water.
- Next apply 2 or 3 coats of the topcoat.

## TECHNICAL DATA

### GOLD AND MIX EFFECT

Binding agent	Acrylic emulsion
Pigments	None
Solvent	Water
Solid components	Approx. 26% by volume
Specific mass	Approximately 1 g/ml
Recommended coat thickness	50 micron wet
Degree of gloss	Eggshell gloss, 35% @ 60°
Dilute with	Water

Hazard classification                      See MSDS

Tool cleaning instructions                Use water and soap

## **STORAGE**

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

## **GENERAL**

Stir thoroughly prior to use. We recommend applying at temperatures between 8°C and 30°C. After use, close the container correctly and store in an upright position in a frost-free area.

## **SURPLUS PRODUCT**

This product and the packaging should be disposed of at a collection point for hazardous or special waste.